

---

# INDEX

---

## A

Abrasion resistance – 3-3 - 3-5, 8-2  
Acceptance testing  
    Low pressure air testing – 11-3 - 11-5  
    Hydrostatic infiltration testing – 11-5  
Acid formation – (see Hydrogen sulfide)  
Acid resistance – 3-3  
Aggressive soils – 3-3, 8-2  
Air testing – 11-3, 11-4,  
ASTM Standards – 1-6

## B

Backfill  
    Compaction – (see Compaction, trench backfill)  
    Final – 7-5  
    Frictional forces – 4-3  
    Initial – 7-5  
    Materials – 6-5  
Bedding  
    Bell or coupling holes – 6-7, 7-4  
    Classes – 6-18  
    Haunching – 6-7 - 6-9  
    Load factors – 6-9, 6-18  
    Materials – 6-4  
    Shovel-slicing – 6-7, 6-11  
Bell holes – (see Bedding, Bell or coupling holes)  
Building sewer, house connections – 10-1

## C

Chemicals – Ch. 3  
Clay pipe – (see Vitrified Clay Pipe)  
Cleaning methods – (see Maintenance)  
Cleanout structure – 9-4  
CLSM (Controlled Low-Strength Material)  
    – 4-8, 4-9, 6-13, 6-14, 6-18  
Compaction, trench backfill – 6-7, 7-5, 7-6  
Compression joint – 2-3, 7-4, 8-2  
Compressive strength – 8-1  
Computerized trench load design – 4-1, 5-1  
Computation table for load coefficients – 4-15  
Concentrated loads – 4-12  
Concrete  
    Cradle – 6-14 - 6-16, 6-18  
    Encasement – 6-15 - 6-16, 6-18

## Construction

    Open trench – Ch. 7  
    Special structures – Ch. 9  
    Trenchless – Ch. 8  
Conveyance factor tables – 2-19  
Conveyance factors – 2-15 - 2-18  
Corrosion – 3-1 - 3-3, 8-2  
    Aggressive soils – 3-3, 8-2  
    Resistance – 8-2  
Corrosive soils – (see Corrosion, Aggressive soils)  
Curvilinear sewers – 1-2, 2-4

## D

Design, computer aided – 2-13  
Design flow – 2-2, 2-8  
Design load vs. Actual load – 6-2  
Design life – 2-1  
Design period – 2-1  
Design, rigid conduit – Ch. 2, Ch. 6  
Design safety factor – 6-17  
Dewatering – 7-6  
Dimension Accuracy – 8-2  
Distributed loads – 4-16  
Drop manhole – 9-1, 9-3  
Dynamic loads (see Impact factors)

## E

Embankment versus trench load – 4-8  
Encasement  
    Concrete – 6-15 - 6-16, 6-18  
    Crushed Stone – 6-12, 6-18, 7-3  
Energy gradient – 2-7, 2-9, 2-10  
Environmental – 1-3  
Excavation, trench – 7-1, 10-2  
Extraneous flows – 2-2,  
Extruding – 1-4

## F

Factor of safety, design – 6-1, 6-2  
Field supporting strength – 6-3, 6-8 - 6-10, 6-18,  
    6-19, 6-20  
Field Verification – 7-7  
    (see also Acceptance testing)  
Final backfill – 7-5  
Firing – 1-5  
Fittings – 1-3, 10-3,

Flexible compression joints – 2-3  
 Flow characteristics – 2-6  
 Flow estimating – 2-6  
 Flow monitoring – 2-6  
 Foundation – 6-4, 7-3, 7-6, 9-2, 10-2  
 Frictional forces – 4-3

## G

Geotextile – 7-7  
 Guided Bore Method –  
   (see Pilot Tube Guided Bore Method)  
 Gravity sewer design – Ch. 2  
 Grinding – 1-4

## H

Haunch – 6-6 - 6-9, 7-5  
 Haunching (see Shovel slicing)  
 High temperature applications – 3-6  
 Hydraulic design – 2-6 - 2-19  
   Calculating flow – 2-6, 2-7  
   Computer aided design – 4-1, 5-1  
   Design requirements – 2-7, 2-9  
   Flow characteristics diagram – 2-6  
   Hydraulic profile – 2-7  
   Manning's coefficient – 2-10  
   Manning's Equations – 2-9  
   Sewer sizing -  
     (see Hydraulic design, Velocity  
     and quantity)  
   Velocity and Quantity – 2-9  
 Hydrogen sulfide – 3-1, 3-2  
 Hydrostatic Infiltration Testing – 11-5

## I

Impact factor – 4-17, 5-1  
 Industrial – 3-1  
 Inert – 1-3  
 Inflow – 2-2  
 Infiltration – 2-2, 11-5, 11-6  
 Initial backfill – 6-6, 7-5  
 Inspection – Ch. 11

## J

Jacking Pipe – 4-10, 4-12, 8-1 – 8-3  
 Joining – 7-4  
 Joints  
   Flexible 1-2  
   Open trench – 2-3, 3-5  
   Trenchless – Ch. 8

## L

Laser – 11-1  
 Lateral sewers – 9-4, 10-1  
 Lifecycle – Foreword-2, Foreword-3, 2-1  
 Load  
   Coefficient,  $C_d$  -4-6  
   Coefficient,  $C_s$  – 4-15  
   Coefficient,  $C_t$  – 4-11  
   Concentrated – 4-12, 4-13, 4-14  
   Design load versus actual load – 6-2  
   Distributed – 4-15, 4-16  
   Effect of trench width – 4-3, 6-2  
   Embankment – 4-8  
   Impact – 4-17  
   Jacked pipe in tunnel – 4-10  
   Superimposed – 4-12, 4-14, 4-15, 4-16  
   Trench load tables – Ch. 5  
 Load Bearing – 1-3, 7-7  
 Load factors – 6-9, 6-18  
   Class B – 6-6, 6-11, 6-12, 6-18, 6-20  
   Class C – 6-6, 6-11, 6-18, 6-20  
   Class D – 6-6, 6-10, 6-18, 6-20  
   CLSM – 4-8, 4-10, 6-6, 6-13, 6-14, 6-18, 6-20, 7-7  
   Concrete Cradle – 6-6, 6-14, 6-15, 6-18  
   Concrete Encasement – 6-15 - 6-18  
   Crushed Stone Encasement – 6-6, 6-12, 6-18, 7-3  
 Low-Pressure Air Testing – 10-3

## M

Maintenance – Ch. 12  
   Balling – 12-5  
   Bucket machine – 12-5  
   Hydro jetting – 12-2  
   Mechanical rodding – 12-4, 12-5  
 Manhole – 7-7, Ch. 9  
   Drop – 9-3  
 Manning's coefficient – 2-10  
 Manning's Equations – 2-9, 2-10  
 Marston's Equation, modified – 4-8, 4-9, 4-12  
 Marston's Equation, rigid pipe – 4-2, 4-4, 4-5, 4-10,  
   5-1, 6-2  
 Mechanical compaction – 7-5, 7-6  
 Microtunneling – 8-8

## N

Native bedding – 6-6  
 NCPI (National Clay Pipe Institute) – Forward-2  
 "n"-factor – 2-10  
   Coefficient – 2-10  
   "n" values – 2-10  
   for Manning's Equation, chart – 2-12

**P**

Peak flow – 2-6, 2-8  
 Penetrometer – 6-14  
 Perforated pipe – 1-5  
 Pilot tube method – 8-4 - 8-7  
 Pipe (see also Vitrified Clay Pipe)  
     Bursting – 8-9  
     Size – 2-8  
 Planning, sewer – 2-1

**Q**

Quantity equation – 2-9

**R**

Residential connections –  
     (See Service connection)  
 Rigid conduit  
     Design – Ch. 4  
     Structural analysis – Ch. 6  
 Root intrusion – 2-3  
 Roughness coefficient – 2-10

**S**

Safety factor – 4-10, 5-1, 6-17  
 Service connection – 7-7, 10-3  
 Service life – Foreword-2, Foreword-3  
 Sewer  
     Acid formation – (see Hydrogen sulfide)  
     Bedding – 6-4  
     Construction – Ch. 7, Ch. 8, Ch. 9  
     Curved – 1-2, 2-4  
     Design flows  
         Minimum & maximum – 2-2  
         Peak – 2-6, 2-7, 2-8  
     Design period – 2-1  
     Flow measurement – 2-6  
     Hydraulic gradient – 2-7  
     Layout – 2-1  
     Line and grade – 7-1, 7-4, 8-4, 8-5 - 8-8  
     Longevity – Foreword-2, Foreword-3,  
         Foreword-4  
     One-hundred year old – Foreword-2, 2-1, 3-1, 12-2  
     Service connections – 7-7  
     Sizing – 2-8  
     Sulfide generation – (see Hydrogen sulfide)  
     Supporting strength – 6-1, 6-3, 6-9, 6-10, 6-18  
     Testing – 1-6, 3-4, 6-3, 7-7, Ch. 11  
     Three edge bearing strength – 6-9, 6-18  
     Trench excavation – 7-1, 10-2  
     Trench sheeting – 6-2, 7-2  
     Velocities, limiting – 2-2, 2-6, 2-9, 2-10

Sheeting – 6-2, 7-2  
 Shovel slicing – 6-7, 7-5  
 Slurry microtunneling – 8-8  
 Soils  
     Backfill classification – 4-7  
     Uniform soil groups – 6-5  
 Spangler – 4-8, 4-9  
 Special structures – Ch. 9  
 Spread diameter – 6-13  
 Static pipe bursting – 8-9  
 Structural design – Ch. 6  
 Superimposed loads – 4-12, 4-14, 4-15, 4-16  
 Supporting strength  
     VCP – 6-3, 6-7, 6-8, 6-9, 6-10, 6-18  
 Sustainability – 1-2

**T**

Tapping – 10-3  
 Testing – 1-5, 1-6, 3-4, 6-3, 6-8, 6-13, 6-14, 7-7,  
     11-3, 11-4, 11-5, 11-6  
 Theodolite – 8-5  
 Three edge bearing strength – 6-18  
 Transition width – 4-4, Ch. 5  
 Trench  
     Backfilling – Ch. 4, Ch. 6, 7-5, 10-2  
     Bottom preparation – (see Trench, Foundation)  
     Box – 6-2, 7-2  
     Compaction – 6-7, 7-5, 7-6  
     Cross section – 4-3, 6-4  
     Excavation – 7-1, 10-2  
     Foundation – 6-4, 7-3, 7-6, 9-2, 10-2  
     Load equation – (see Trench load equation)  
     Load tables – (see Trench load tables)  
     Sheeting, effect of removal – 6-2, 7-2  
     Walls, effect of slope – 6-3, 7-2  
     Width, effect on load – Ch. 5, 6-2  
 Trench load tables – Ch. 5  
 Trench load equation – 4-8, 4-9  
 Trench versus embankment load – 4-2, 4-8  
 Trenchless installation – Ch. 8

**U**

Uniform flow – 2-6, 2-7  
 Uniform soils – 6-5  
 Unstable foundation – 6-4

**V**

Velocity – 2-9, 2-13, 3-2, 12-5  
     Limits in sewers – 3-3  
 Velocity equation – 2-9  
 Velocity variations chart – 2-10

Vitrification – Foreword-2, 1-3, 1-4, 1-5

Vitrified clay pipe

Advantages – Ch. 1

Characteristics – Ch. 1

Flexible joints (see Curvilinear sewers)

Inert – 1-3

Jacking Pipe – 4-10, 8-1, 8-2, 8-3

Joining – 7-4

Manufacture – 1-4, 1-5

Properties – 1-1 - 1-3

Rigid Strength – 1-1

Specifications and standards – 1-6

Sustainable – Foreword-4, 1-2, 1-3

## **W**

Well points – 7-6

Wheel loads – 4-12, 4-13, 4-16, 4-17